

TECHNICAL DATA SHEET

Biofuel Fat

An alternative source of reliable energy made from rendered animal by-products and used cooking oil. Bio-fuel fat can be used interchangeably with #6 oil and with minor boiler configurations, can be used in place of #2 oil and Natural Gas.

LABORATORY ANALYSIS REPORT

<u>TEST</u>	<u>METHOD</u>	<u>RESULT</u>
GRAVITY, API AT 60 F	D-1298	22.5
FLASH PT., PENSKY MARTENS, DEG F	D-93	>200
SULFUR, X-RAY, WT PCT	D-4294	<0.010
WATER & SEDIMENT (BS&W), VOL PCT	D-1796	0.2
ASH, WT PCT	D-482	0.022
B.T.U. VALUE (GROSS) BTU/LB	D-4868	17,000
B.T.U. VALUE (GROSS) BTU/GAL	D-4868	130,000
VANADIUM, PPM	SOL/DIL	<1
POUR POINT, DEG C/F	D-97	15C/59F

Conducted and prepared by Saybolt, Inc.

Making a Sustainable Difference.

P.O. Box 3588 (22604-2586)
 151 Valpro Drive
 Winchester, VA 22603
 ☎ 540.877.2590
 📠 540.877.3215
valleyproteins.com